

FLOTT Potato Washer and Peeler

- accumulated water bath peeling at the bottom and sides for:
 - short, low-noise peeling cycles
 - delicate peeling action
 - reduced water consumption
- auto-stop control for complete safety:
 - the machine automatically stops when the loading lid, top lid or release flap are opened
- stainless steel body
- 400 V three phase AC motor with belt drive
- automatic shut down with manual guards against automatic start-up after a power failure
- motor protection
- 3 metres of cable with Cekon plug
- control valve for reduced water consumption
- automatic peeling-time selector, gentle release

Equipments for selection

- 1.) round hole peeling system, stainless steel
 - 1 round hole peeling basket
 - 3 round hole peeling discs No. 1-2-3 for new, medium and old potatoes
 - 1 support disc
 - 1 cap nut
- 2.) carborundum peeling system, stainless steel
 - 1 carborundum peeling basket
 - 1 carborundum peeling disc
 - 1 cap nut
- 3.) SUPER peeling system with double-edged blades, stainless steel
 - for right and left rotation
 - 1 SUPER peeling basket with double-edged blades
 - 1 SUPER peeling disc with double-edged blades
 - 1 SUPER cap nut

Possible accessories

- 1.) 1 peel collector
 - a.) plastic
 - b.) plastic with starch-separator, stainless steel
 - c.) stainless steel
- 2.) 1 wash insert, stainless steel (basket and disc for washing potatoes and other root vegetables without simultaneous peeling)

The machine is also available with a dirty water drain on the left-hand side.

| Machine type | 16 K | 18 K | 20 K | 25 K |
|-----------------------------------|-------------|-------------|-------------|-------------|
| Loading capacity kg | 6 | 10 | 15 | 25-30 |
| Raw product output per hour up to | 150 | 280 | 400 | 800 |
| Rated power kW | 0,25 | 0,37 | 0,55 | 1,5 |
| Water connection DN standard | 15 | 15 | 20 | 25 |
| Depth mm | 372 | 530 | 600 | 735 |
| Width mm | 435 | 555 | 650 | 750 |
| Height mm | 855 | 930 | 950 | 1195 |